

SHEET NOTES

- 1. SEE SHEET CO.1 FOR GENERAL SHEET NOTES.
- 2. CURB HEIGHTS ARE 6" UNLESS NOTED OTHERWISE.
- LANDINGS ON ACCESSIBLE ROUTES SHALL NOT EXCEED 2% IN ANY DIRECTION.
- 4. ALL ACCESSIBLE ROUTES SHALL COMPLY WITH CURRENT ADA ACCESSIBILITY GUIDELINES FOR BUILDING AND FACILITIES (ADAAG).
- 5. ALL WALKWAYS FROM ACCESSIBLE UNITS ARE DESIGNED TO NOT REQUIRE HANDRAILS, THEREFORE, RAMPS WITH SLOPES STEEPER THAN 5.0% AND LESS THAN 8.33% SHALL NOT EXCEED 0.5' RISE OR 6.0' LENGTH.
- 6. FINISH CRADES ARE TO BE BROUGHT TO WITHIN 0.08 FT IN 10 FT OF THE GRADES SHOWN AT SUBGRADE AND TO WITHIN 0.03 FT IN 10 FT AT FINISH GRADE. CONTRACTOR TO ALLOW FOR PLACEMENT OF REQUIRED TOPSOIL IN ROUGH GRADING.
- 7. GRADING ELEVATIONS AS SHOWN ON SITE AND LANDSCAPE PLANS ARE FINSHED GRADE WHICH INCLUDES SUBGRADE SOIL, TOPSOIL, SOIL AUBENDRENTS, ROCKERY AND RUNOFF PROTECTION CONTRACTOR IS RESPONSIBLE TO COORDINATE GRADING WITH BOTH EXCAVATOR AND LANDSCAPE CONTRACTOR.

GRADING LABEL LEGEND

بالكبيبية	•
xxxx xx	DESCRIPTION LISTED BELOW.
BS BW DSX FF G SY TC TP TSX TW	BOTTOM OF STAIRS FINISHED GRADE AT BOTTOM OF WALL DOOR SILL EXISTING GRADE FINISHED FLOOR ELEVATION FINISH GRADE GROUND SIDEWALK TOP OF CURB TOP OF PAYEMENT TOP OF STAIRS FINISHED GRADE AT TOP OF WALL

LEGEND

LEGEND	
EXISTING CONTOUR MINOR	
EXISTING CONTOUR MAJOR	100
PROPOSED CONTOUR MINOR	102
PROPOSED CONTOUR MAJOR	100
GRADE BREAK	<u> </u>
SEDIMENT FENCE PER DETAIL 5/C4.0	-9-0-2-5-0-2-
INLET PROTECTION PER DETAIL 3/C4.0	0
BIOBAGS PER DETAIL 2/C4.0	c5 2 3
CONSTRUCTION ENTRANCE PER DETAIL 4/C4.0	

GRADING PLAN

ATE:	08/20/2019
RAWN:	JJS
HECKED:	NWS



SHEET NUMBER

JOB NUMBER: A19133.10

(IN FEET) 1 inch = 20 feet



EXGINEERING
h Drow | Sulfe 300 | Beaverlon, OR | 97006
tel | 600 620 6599 | fix | www.aseng.com K ∢ 4875 SW Gniffth Drov 503 620 3030 tel | f

CAMAS

ACADEMY KIDDIE

SHEET TITLE

REVISIONS:

C AS PERSONNELLE.