EXHIBIT 7

27 Watt **LED** Wall Light

Replaces up to 100W MH

WLSG27LED

Lumens: 1660   **Lumens/Watt: 59**
Watts: 27.75   **CRI: 68**

LED info

Atlas LED provides higher lumen output, greater energy efficiency and more reliable fixture performance. All Atlas LED modules are manufactured with an Epoxy Guard™ conformal coating which reduces the chance of future corrosion.

Atlas' LEDs operate at 4100K CCT providing a natural white light similar to that of moonlight.

Delivers 70% or greater of initial lumens at 60,000 hours

Driver

Constant current, Class 2, 120-277 VAC, 50-60 Hz

High Efficiency ~ 90%

Construction

Traditional fixture designs provide a familiar look and standard installation requirements. Retaining this look allows the ability to upgrade fixtures gradually, while retaining the same overall fixture appearance throughout a facility.

Optics

Lens assembly is designed to provide high efficiency and to target the light needed to satisfy outdoor lighting requirements.

Glare Free

Positioning of the LEDs results in the light being directed to desired locations eliminating glare and offensive light.

Thermal Management

Atlas' exclusive Thermal Stacking Technology™ system features a unique internal design that allows for lower operating temperatures which results in a brighter, whiter light, more stable color and longer LED and driver life.

Patent Pending

Atlas wall lights are protected by patents pending in US, Canada, China, Mexico and 140 other countries

Dimensions and Specifications:

Overall Height: 8.5" (21.59 cm)
Overall Width: 8.75" (22.225 cm)
Depth: 9.05" (23.0632 cm)
Weight: 6.6 lbs.

Dura Finish DF | **THERMAL STACKING** | **Illuminating** ENGINEERING SOCIETY LM-79-2008 LM-80-2008 | **60,000+ HOURS** | **MULTI VOLT 120 – 277** | **UL LISTED** | **5 YEAR WARRANTY** | **quick SHIP**